



## DECLARATION OF PERFORMANCE

No. 01604

- |   |   |
|---|---|
| 1. Unique identification code of the product-type:                      | UniBond Neutral (01604)   |
| 2. Intended use/es:   | Sealant for facade for interior and exterior application (F-EXT-INT)<br>Sealant used for sealing glazing applications (G) |
| 3. Manufacturer:  | Henkel AG & Co. KGaA<br>D-40191 Düsseldorf  |
| 4. Authorised representative:   | Not relevant  |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3<br>Reaction to fire: System 3  |
| 6a. Harmonised standard/s:  | EN 15651-1:2012<br>EN 15651-2:2012  |
| Notified body/ies:  | Type-testing: SKZ - Testing GmbH, 1213<br>Reaction to fire : SKZ - Testing GmbH, 1213                                     |
| 6b. European Assessment Document:                                       | Not relevant  |
| European Technical Assessment:  | Not relevant  |
| Technical Assessment Body:  | Not relevant  |
| Notified body/is:   | Not relevant  |
| 7. Declared performance/s:  |   |

Conditioning: Method A

Substrate: Aluminium/Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
<b>Reaction to fire</b>	Class E	System 3	EN 15651-1:2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	System 3	
<b>Water tightness and air tightness</b>			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 25 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
<b>Durability</b>			
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		

Conditioning: Method A  
Substrate: Aluminium/Glass; without primer


Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
<b>Reaction to fire</b>	Class E	System 3	EN 15651-2:2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	System 3	
<b>Water tightness and air tightness</b>			
Loss of volume	≤ 40 %		
Resistance to flow	≤ 3 mm		
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF		
Elastic recovery	≥ 60 %		
<b>Durability</b>			
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley  
Global Head of Marketing ACG I  
\_\_\_\_\_  
(name and function)




\_\_\_\_\_  
(signature)

Dr. Michael Frank  
Director Global Product Development  
\_\_\_\_\_  
(name and function)



\_\_\_\_\_  
(signature)

\_\_\_\_\_  
Düsseldorf, 19.9.2022  
(place and date of issue)

 1213	
Henkel AG & Co. KGaA D-40191 Düsseldorf 20 01604  UniBond Neutral (01604)	
EN 15651-1:2012 Sealant for facade for interior and exterior application	
<b>Reaction to fire</b>	Class E
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 25 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
<b>Durability</b>	
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
EN 15651-2:2012 Sealant used for sealing glazing applications	
<b>Reaction to fire</b>	Class E
<b>Water tightness and air tightness</b>	
Loss of volume	≤ 40 %
Resistance to flow	≤ 3 mm
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF
Elastic recovery	≥ 60 %
<b>Durability</b>	
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
<a href="http://www.henkel-dop.com">www.henkel-dop.com</a>	