



DECLARATION OF PERFORMANCE

No. 00659

1. Unique identification code of the product-type: Unibond Easy Smooth All Purpose Sealant Ready To Use 200ml
2. Intended use/es: Sealant for facade for interior application only (F-INT)
Sealant for joints in sanitary areas (S)
3. Manufacturer: Henkel AG & Co. KGaA
D-40191 Düsseldorf
4. Authorised representative: Not relevant
5. System/s of assessment and verification of constancy of performance: Type-testing: System 3
Reaction to fire: System 3
- 6a. Harmonised standard/s: EN 15651-1: 2012
EN 15651-3: 2012
- Notified body/ies: Type-testing: SKZ-TeConA GmbH, 1213
Reaction to fire : SKZ-TeConA GmbH, 1213
- 6b. European Assessment Document: Not relevant
European Technical Assessment: Not relevant
Technical Assessment Body: Not relevant
Notified body/is: Not relevant
7. Declared performance/s:

Conditioning: Method B

Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1: 2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 5 mm		
Loss of volume	≤ 45 %		
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %		
Durability	pass		

Conditioning: Method B
Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3: 2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
Microbiological growth	0		
Durability	pass		


8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ian Lapsley
Global Head of Marketing ACG I

(name and function)



(signature)

Dr. Bernhard Schöttmer
Director Global Product Development

(name and function)



(signature)

Düsseldorf, 2.10.2019
(place and date of issue)

 1213	
Henkel AG & Co. KGaA D-40191 Düsseldorf 13 00659 Unibond Easy Smooth All Purpose Sealant Ready To Use 200ml	
EN 15651-1: 2012 Sealant for facade for interior application only	
- Type	F-INT
- Conditioning:	Method B
- Substrate:	Aluminium; without primer
Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 5 mm
Loss of volume	≤ 45 %
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %
Durability	pass
EN 15651-3: 2012 Sealant for joints in sanitary areas	
- Type	S
- Conditioning:	Method B
- Substrate:	Aluminium; without primer
Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
Microbiological growth	0
Durability	pass
www.henkel-dop.com	