



DECLARATION OF PERFORMANCE

No. 00659

- | | |
|---|--|
| 1. Unique identification code of the product-type: | Unibond Easy Smooth All Purpose Sealant Ready To Use 200ml |
| 2. Intended use/es: | Sealant for facade for interior application only (F-INT)
Sealant for joints in sanitary areas (S) |
| 3. Manufacturer: | Henkel AG & Co. KGaA
D-40191 Düsseldorf |
| 4. Authorised representative: | Not relevant |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3
Reaction to fire: System 4 |
| 6a. Harmonised standard/s: | EN 15651-1:2012
EN 15651-3:2012 |
| Notified body/ies: | Type-testing: SKZ-TeConA GmbH, 1213 |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified body/ies: | Not relevant |
| 7. Declared performance/s: | |
| Conditioning: Method B
Substrate: Aluminium; without primer | |

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class F	System 4	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 5 mm		
Loss of volume	≤ 45 %		
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %		
Durability	pass		



Conditioning: Method B
Substrate: Aluminium; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class F	System 4	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
Microbiological growth	0		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Baptiste Chièze
International Brand Manager

(name and function)

(signature)

Dr. Bernhard Schöttmer
Director Global Product Development

(name and function)

(signature)

Düsseldorf, 23.8.2016

(place and date of issue)

 1213	
Henkel AG & Co. KGaA, D-40191 Düsseldorf 13 00659 Unibond Easy Smooth All Purpose Sealant Ready To Use 200ml	
EN 15651-1:2012 Sealant for facade for interior application only - Type: F-INT - Conditioning: Method B - Substrate: Aluminium; without primer	
Reaction to fire	Class F
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 5 mm
Loss of volume	≤ 45 %
Tensile properties (i.e. elongation) at break at 23°C	≥ 25 %
Durability	pass
EN 15651-3:2012 Sealant for joints in sanitary areas - Type: S - Conditioning: Method B - Substrate: Aluminium; without primer	
Reaction to fire	Class F
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
Microbiological growth	0
Durability	pass