



## DECLARATION OF PERFORMANCE

No. 00674

- |   |  |
|---|--|
| 1. Unique identification code of the product-type:                      | UniBond Universal All Purpose Sealant (00674)  |
| 2. Intended use/es:   | Sealant for facade for interior and exterior application (F-EXT-INT)<br>Sealant for joints in sanitary areas (S)                 |
| 3. Manufacturer:  | Henkel AG & Co. KGaA<br>D-40191 Düsseldorf   |
| 4. Authorised representative:   | Not relevant   |
| 5. System/s of assessment and verification of constancy of performance: | Type-testing: System 3<br>Reaction to fire: System 3   |
| 6a. Harmonised standard/s:  | EN 15651-1: 2012<br>EN 15651-3: 2012   |
| Notified body/ies:  | Type-testing: FUNDACION TECNALIA RESEARCH & INNOVATION, 1292<br>Reaction to fire : LGAI TECHNOLOGICAL CENTER, S. A./Applus, 0370 |
| 6b. European Assessment Document:                                       | Not relevant   |
| European Technical Assessment:  | Not relevant   |
| Technical Assessment Body:  | Not relevant   |
| Notified body/is:   | Not relevant   |
| 7. Declared performance/s:  |  |

Conditioning: Method A  
Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
<b>Reaction to fire</b>	Class E	System 3	EN 15651-1: 2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD	System 3	
<b>Water tightness and air tightness</b>			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 25 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
<b>Durability</b>	pass		

Conditioning: Method A  
Substrate: Glass; without primer

Essential characteristics	Performance	System/s of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-3: 2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF		
Microbiological growth	1		
Durability	pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Duggan-Hill  
Global Steering Unit Head - ACG  
\_\_\_\_\_  
(name and function)



\_\_\_\_\_  
(signature)

Dr. Bernhard Schöttmer  
Director Global Product Development  
\_\_\_\_\_  
(name and function)



\_\_\_\_\_  
(signature)

\_\_\_\_\_  
Düsseldorf, 5.8.2019  
(place and date of issue)

 1292, 0370	
Henkel AG & Co. KGaA D-40191 Düsseldorf 13 00674  UniBond Universal All Purpose Sealant (00674)	
EN 15651-1: 2012 Sealant for facade for interior and exterior application - Type: F-EXT-INT - Conditioning: Method A - Substrate: Glass; without primer	
<b>Reaction to fire</b>	Class E
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 25 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
<b>Durability</b>	pass
EN 15651-3: 2012 Sealant for joints in sanitary areas - Type: S - Conditioning: Method A - Substrate: Glass; without primer	
<b>Reaction to fire</b>	Class E
<b>Water tightness and air tightness</b>	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20 %
Tensile properties (i.e. elongation) at maintained extension after water immersion	NF
Microbiological growth	1
<b>Durability</b>	pass
www.henkel-dop.com	